





MECHANICAL:



NOTE: ONE RACKMOUNT PLATE AND TWO DISTRIBUTION HUBS



ELECTRICAL:

INSERTION LOSS:

- < 13 dB, 5 MHz TO 40 MHz
- < 14 dB, 40 MHz TO 260 MHz
- < 17 dB, 260 MHz TO 550 MHz
- < 19 dB, 550 MHz TO 860 MHz

FLATNESS:

+/- .15 dB MAXIMUM, ALL PORTS

VIDEO PINOUT:

RJ-45 PIN 7 AND PIN 8

US PATENTS 5,495,212 AND 5,633,614 AND 6,150,896

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: 1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND 2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRED OPERATION.

APPLICATION:

Rackmount RF video and data distribution hub for use in CATV/MATV systems with distances of up to 100 meters on CAT5 or better grade cable. (Product testing in specific applications is recommended.)

BH [®] BH ELECTRONICS, INC.
 BURNSVILLE & MARSHALL, MN
 ©1998 BH Electronics

TITLE: Lynx [®] 16 PORT RACKMOUNT VIDEO AND DATA HUB

PART NO: 040-0119 DATE: 5/03